



Inami & Co., Ltd.



L-4550

INTERNAL READING LENSMETER

INTERNAL READING LENSMETER L-4550



Specifications of L-4550 (Cross Line Target)

1. Complete analysis of lenses.
 - A. Determination of sphere power.
Range of measurement of vertex power:
0 to $\pm 25.00D$.
Up to $\pm 3.00D$. in 0.125D. steps and over $\pm 3.00D$. in 0.25D. steps.
 - B. Determination of cylinder power.
 - C. Determination of cylinder axis: 0° to 180° in 1° step.
 - D. Determination of prism power: 6Δ (read in view field).
Prism compensator: Maximum 15Δ in 1Δ step.
2. Instrument tilting angle: Freely adjustable between 30° to 90° .
3. Measurable lens diameter: 32mm to 90mm.
4. Accurate centering and marking of lenses.
5. Bulb: 110V, 220V, 240V-15W. (L4530V0)
6. Size: 413mm(H:at 90°) 335mm(H:at 30°) \times 160mm(W) \times 422(D)mm.
7. Weight: 4.9kg.
8. Accessories: 2 spare bulbs, a fuse and a dust cover.
9. Optional accessories: Prism Compensator.



Prism Compensator



L4530V0 Bulb



Certified Management System
DIN EN ISO 9001:2000
JIS Q 9001:2000
EN ISO 13485:2000
ISO 13485:2003



"A Passion for a Nice View"

● Specifications subject to change without prior notice.



Inami & Co., Ltd.

No. 24-2, Hongo 3-Chome,
Bunkyo-ku, Tokyo 113-0033, Japan
Tel. 81-3-3814-5916 Fax. 81-3-5684-2126
Website : <http://www.inami.co.jp>
E-Mail : corpinfo@inami.co.jp
®TRADE MARK OF INAMI & CO.,LTD.

ZFG1000